| ARTICLE CODE | DESCRIPTION |
| --- | --- |
| PXP-6300 | Pallet Export line - 800x600x160mm - open deck - 3 skids - recycled |

## BRAND

Cabka



## PRODUCT DESCRIPTION

Reusable pallet suitable for long-term use
Impact-resistant material - without metal reinforcements
Universal, durable and environmentally friendly solution for storage, distribution, closed loops or export, pharmaceuticals & laboratory, healthcare sector, etc.
Suitable for intensive use in high-rotation logistics, semi-hygienic environments
Temperature resistant from -20°C to +40°C, cleaning up to +65°C (max. 10 min.) and short-term surface steaming up to +100°C
Weather and UV resistant
Easy cleaning
Rounded impact zones reduce risk of damage to a minimum
Raised edges ensure optimal transport security and stability
Options: anti-slip structures, customisation, etc.
100% recyclable at end of life
Entry height short side: 115 mm
Entry height long side, between runner and deck: 93 mm
Maximum static load: 2000 kg
Maximum dynamic load: 1000 kg
Maximum racking load: 500 kg
Packaging: 15 pallets/stack

## SPECIFICATIONS

| | |
| --- | --- |
| Length (mm) | 800 |
| Width (mm) | 600 |
| Height (mm) | 160 |
| Net weight (kg) | 8 |
| Matter | Recycled polypropylene |
| Color | Anthracite |

## TECHNICAL DETAILS

| | |
| --- | --- |
| ETIM | EC004004 |
| MOQ sales (Pc.) | 1 |

## ATTRIBUTES

| | |
|---|---|
| Model | Export line |
| Gs Certificate | false |
| Quantity Par Stack | 30 |
| Load Capacity Static (kg) | 2000 |
| Load Capacity Dynamic (kg) | 1000 |
| Type Of Surface | Open deck |
| Nestable | false |
| Load Capacity In Rack (kg) | 500 |
| Entry Height | Entry height short side: 115 mm // Entry height long side, between the runner and the deck: 93 mm // |
| Quantity Skids | 3 |