| ARTICLE CODE | DESCRIPTION |
| --- | --- |
| HMT-8030 | Maxi transport unit - 1100x260x293mm - max load 250 kg |

## BRAND

Lite work designs

## PRODUCT DESCRIPTION

Use this transport aid to move heavy loads safely, easily and efficiently
Ideal for use by one person, from pallet to installation
Reduces the risk of personal injury or damage to the heat pump
Complies with UK/EU Manual Handling / Health and Safety regulations
The transport unit takes 80% of the weight on itself
Highly manoeuvrable and suitable for all terrains: mud, gravel, grit, grass, ...
Save time and energy, because moving the heat pump is now possible by one person
Professional appearance: no lashing straps, forklift or a team of people required
Max. load capacity: 400 kg (static & dynamic)
Useful loading width: 820 mm
The transport unit is supplied with securing strap, pull strap and handle, 2 Allen Keys (for maintenance purposes) and 1 accessory bag









## SPECIFICATIONS

| | |
| --- | --- |
| Length (mm) | 1100 |
| Width (mm) | 260 |
| Height (mm) | 293 |
| Net weight (kg) | 11 |
| Color | Undefined |

## TECHNICAL DETAILS

| | |
| --- | --- |
| ETIM | EC001203 |
| MOQ sales (Pc.) | 1 |

## ATTRIBUTES

| | |
|---|---|
| Quantity Handles | 1 |
| Food safe certified | false |
| Fits article | Goods up to 820mm wide |
| Load bearing capacity (kg) | 400 |
| Type of tyres | Off-road wheels and tyres |
| With brake | false |
| TÜV certification | false |
| Material wheel forks | ZINC |
| Material frame | REG |
| Material transport plain | REG |
| Quantity fixed wheels without brake | 2 |
| Quantity swivel wheels without brake | 0 |